



Ursa[®] Ultra X SAE 5W-30

Premium performance fuel efficient synthetic diesel engine oil

Product description

Ursa Ultra X SAE 5W-30 is a premium performance fuel efficient, low emissions synthetic heavy-duty diesel engine oil. It is designed to meet the performance requirements of a wide range of diesel and gas powered engines in off-highway and construction applications, while offering improved fuel economy with lower exhaust emission output.

Ursa Ultra X SAE 5W-30 is formulated for use in most Euro V and some Euro VI trucks fitted with advanced after-treatment systems where low emission diesel lubricants are required.

Ursa Ultra X SAE 5W-30 is formulated with premium performance synthetic base oils and advanced technology dispersant and detergent additives, with robust oxidation, wear and corrosion inhibitors, viscosity improver and foam suppression additives.

Customer benefits

- Designed to deliver improved fuel efficiency with low emissions performance, helping reduce total cost of ownership
- Formulated for optimum engine wear and corrosion protection with reliable foam suppression performance
- Low viscosity synthetic base oils promote rapid oil circulation and wear protection during cold or sub-zero engine start-ups
- Advanced piston cleanliness and good wear control offers optimum engine service life with lower maintenance downtime

Product highlights

- **Fuel efficiency with low emissions performance**
- **Offers optimum wear and corrosion protection**
- **Promotes cold or sub-zero engine start protection**
- **Formulated for optimum engine service life**
- **Helps reduce emission system service downtime**
- **Designed to control oxidation, sludge and oil thickening**

Selected specification standards include:

ACEA	API
Cummins	DAF
Deutz	IVECO
JASO	Mack
MAN	Mercedes Benz
MTU	Renault
Volvo	

- Advanced formulation helps reduce emission control system service downtime and offers improved Diesel Particulate Filter (DPF) life
- Premium additive design with synthetic base stocks help control oxidation, sludge and oil thickening, improving vehicle uptime

Applications

- Ursa Ultra X SAE 5W-30 is a diesel engine oil recommended for four-stroke naturally aspirated and turbocharged diesel engines
- Ursa Ultra X SAE 5W-30 is recommended for use in modern low emission diesel engines (most Euro V and Euro VI trucks fitted with advanced after-treatment systems such as DPFs and Selective Catalytic Reduction (SCR) NOx reduction systems. It is also backwards compatible in older engines in service in markets using Euro V quality Diesel Fuel or Ultra Low Sulphur Diesel (ULSD), and many bio-fuel formulations
- Ursa Ultra X SAE 5W-30 is recommended for use in gas engines and in off-highway or construction applications in conditions where SAE 5W-30 is recommended. However, recommendations may differ between engine manufacturers, so driver manuals and/or dealerships should be consulted if in doubt

Approvals, performance and recommendations

Approvals

- Cummins CES 20077
- Deutz DQC III-10 LA
- Mercedes Benz MB-Approval 228.51
- Mack EO-N
- MAN M3271-1, M3477
- Renault RLD-2
- Volvo VDS-3

Performance

- ACEA E7, E6
- API CI-4
- JASO DH-2
- MTU Category 3.1

Recommendations

Suitable for use in:

- Applications requiring Renault VI RGD and RXD
- Applications requiring Renault VI RD, RD-2, RLD
- Applications requiring Volvo VDS-2
- DAF Extended Drain (Euro III, IV, V and VI engines)
- IVECO Euro VI engines

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 5W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.854
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	75.0
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	12.1
Viscosity Index	ASTM D2270	158
Pour point, °C	ASTM D5950	-43
Flash point COC, °C	ASTM D92	228
Total Base Number, mg KOH/g	ASTM D2896	9.8
Sulphated Ash, %wt	ASTM D874	1.0

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product